



PACKAGES LIMITED (BU-Folding Carton)	Document type RAW MATERIAL SPECIFICATIONS
	Title ANTI SET-OFF POWDER FOR PRINT DRYING IN OFFSET PRINTING DEPARTMENT

Prepared by Asad Javed Manager R&D&QA 	Approved by Salman Fazul -ur Rehman BUMFC 	PAGE 1 (1)	REV 4	DATE 01.07.2024	DOC NO. SPQA/BU-FC/RM/07
--	---	-------------------	--------------	------------------------	---------------------------------

Reviewed on (Date): Reviewed by:	Reviewed on (Date): Reviewed by:	Reviewed on (Date): Reviewed by:	Reviewed on (Date): Reviewed by:
Approved on (Date):  Approved by:	Approved on (Date): Approved by:	Approved on (Date): Approved by:	Approved on (Date): Approved by:

CRITICAL PARAMETERS:

PARAMETER	UNIT	TEST METHOD	STANDARDS	
			*AS-100	CD-30
RETENTION (160 - 170 MESH) MAX.	%	WIQA/BU-FC/8.2.4/13	0.05 MAX.	0.1
MOISTURE MAX.	%	WIQA/BU-FC/8.2.4/12	13.0 MAX.	17.0

PACKING INSTRUCTIONS:

- | |
|--------------------------------------|
| 1. Sealed plastic bags. |
| 2. Suitable to avoid transit damage. |

* The standards will remain unchanged for equivalent grades from any supplier.

**CONTROLLED
DOCUMENT**

 BUSINESS UNIT FOLDING CARTON (BUFC)